



600/1000V LSZH Insulated, Non-sheathed Power Cables (Single Core)

FTX300 1Z1-R (CU/LSZH 600/1000V Class 2)



APPLICATION

The cables is mainly used in power stations, mass transit underground passenger systems, airports, petrochemical plants, hotels, hospitals, and high-rise buildings.

STANDARDS

Basic design adapted to BS 7211

FIRE PERFORMANCE

Flame Retardance (Single Vertical Wire Test)	EN 60332-1-2; IEC 60332-1-2; BS EN 60332-1-2; VDE 0482-332-1 ; NBN C 30-004 (cat. F1); NF C32-070-2.1(C2); CEI 20-35/1-2; EN 50265-2-1*; DIN VDE 0482-265-2-1*
Reduced Fire Propagation (Vertically-mounted bundled wires & cable test)	EN 60332-3-24 (cat. C); IEC 60332-3-24; BS EN 60332-3-24; VDE 0482-332-3; NBN C 30-004 (cat. F2); NF C32-070-2.2(C1); CEI 20-22/3-4; EN 50266-2-4*; DIN VDE 0482-266-2-4
Halogen Free	IEC 60754-1; EN 50267-2-1; DIN VDE 0482-267-2-1; CEI 20-37/2-1 ; BS 6425-1*
No Corrosive Gas Emission	IEC 60754-2; EN 50267-2-2; DIN VDE 0482-267-2-2; CEI 20-37/2-2 ; BS 6425-2*
Minimum Smoke Emission	IEC 61034-1&2; EN 61034 -1&2; DIN VDE 0482-1034-1&2; CEI 20-37/3-1&2; EN 50268-1&2*; BS 7622-1&2*
No Toxic gases	NES 02-713; NF C 20-454

Note: Asterisk * denotes superseded standard.

VOLTAGE RATING

600/1000V



CABLE CONSTRUCTION

Conductor: Plain annealed copper wire, stranded according to IEC(EN) 60228 class 2.

Insulation: Extruded cross-linked XLPE compound.

COLOUR CODE

Insulation Colour as per BS7671

	With Earth Conductor	Without Earth Conductor
2Cores	-	Brown, Blue
3Cores	Yellow/Green, Brown, Blue	Brown, Gray, Black
4Cores	Yellow/Green, Brown, Gray, Black	Brown, Gray, Black, Blue
5Cores	Yellow/Green, Brown, Gray, Black, Blue	Brown, Gray, Black, Blue, Black
Above 5 Cores	Yellow/Green, Black Numbered	Black Numbered

Sheath Colour: Black (other colors upon request)

PHYSICAL AND THERMAL PROPERTIES

Temperature range during operation: Max.90°C
250°C in short-circuit for 5s max.

Minimum bending radius: 8 x Overall Diameter (unarmoured cable)
10 x Overall Diameter (armoured cable)

CONSTRUCTION PARAMETERS

Conductor		FTX300 1Z1-R		
No. of Core X Cross Section	No./Nominal Diameter of Strands	Nominal Insulation Thickness	Insulated, Non-Sheathed	
			Nominal Overall Diameter	Approx. Weight
Noxmm ²	No./mm	mm	mm	kg/km
1x1.5	7/0.53	0.7	3.1	22
1x2.5	7/0.67	0.8	3.7	34
1x4	7/0.85	0.8	4.3	50
1x6	7/1.04	0.8	4.8	70
1x10	7/1.35	1.0	6.2	116
1x16	7/1.70	1.0	7.2	174
1x25	7/2.14	1.2	9.0	276
1x35	7/2.52	1.2	10.0	366
1x50	19/1.78	1.4	11.9	502
1x70	19/2.14	1.4	13.7	706
1x95	19/2.52	1.6	16.0	974
1x120	37/2.03	1.6	17.6	1213
1x150	37/2.25	1.8	19.6	1492

1x185	37/2.52	2.0	21.8	1868
1x240	61/2.25	2.2	24.4	2443
1x300	61/2.52	2.4	27.7	3055
1x400	61/2.85	2.6	31.1	3888
1x500	61/3.20	2.8	34.6	4880
1x630	127/2.52	2.8	38.6	6229

ELECTRICAL PROPERTIES

Conductor Operating Temperature : 90°C

Ambient Temperature : 30°C

Current-Carrying Capacities (Amp)

Conductor cross-sectional area	Reference Method 4 (enclosed in conduit in thermally insulating wall etc)		Reference Method 3 (enclosed in conduit on a wall or in trunking etc)		Reference Method 1 (clipped direct)		Reference Method 11 (on a perforated cable tray, horizontal or vertical)		Reference Method 12 (free air)			
	Horizontal flat spaced	Vertical flat spaced	Trefoil	Horizontal flat spaced	Vertical flat spaced	Trefoil	Horizontal flat spaced	Vertical flat spaced	Trefoil	Horizontal flat spaced	Vertical flat spaced	Trefoil
	2 cables, single-phase a.c. or d.c.	3 or 4 cables, 3-phase a.c.	2 cables, single-phase a.c. or d.c.	3 or 4 cables, 3-phase a.c.	2 cables, single-phase a.c. or d.c. flat and touching	3 or 4 cables, 3-phase a.c. flat and touching or trefoil	2 cables, single-phase a.c. or d.c. flat and touching	3 or 4 cables, 3-phase a.c. flat and touching or trefoil	2 cables, single-phase a.c. or d.c. or 3 cables three phase	2 cables, single-phase a.c. or d.c. or 3 cables three phase	3 cables, trefoil 3-phase a.c.	
1	2	3	4	5	6	7	8	9	10	11	12	
mm ²	A	A	A	A	A	A	A	A	A	A	A	
1.5	18	17	22	19	25	23	-	-	-	-	-	
2.5	24	23	30	26	34	31	-	-	-	-	-	
4	33	30	40	35	46	41	-	-	-	-	-	
6	43	39	51	45	59	54	-	-	-	-	-	
10	58	53	71	63	81	74	-	-	-	-	-	
16	76	70	95	85	109	99	-	-	-	-	-	
25	100	91	126	111	143	130	158	140	183	163	138	
35	125	111	156	138	176	161	195	176	226	203	171	



50	149	135	189	168	228	209	293	215	274	246	209
70	189	170	240	214	293	268	308	279	351	318	270
95	228	205	290	259	355	326	375	341	426	389	330
120	263	235	336	299	413	379	436	398	495	453	385
150	300	270	375	328	476	436	505	461	570	524	445
185	341	306	426	370	545	500	579	530	651	600	511
240	400	358	500	433	644	590	686	630	769	711	606
300	459	410	573	493	743	681	794	730	886	824	701
400	-	-	684	584	868	793	915	849	1065	994	820
500	-	-	783	666	990	904	1044	973	1228	1150	936
630	-	-	900	764	1130	1033	1191	1115	1423	1338	1069

Voltage Drop (Per Amp Per Meter)

Size of conductor	2 cables d.c.	2 cables, single-phase a.c.						3 or 4 cables, 3-phase a.c.								
		Ref. Methods 3 and 4 (enclosed in conduit etc, in or on a wall)			Ref. Methods 1 and 11 (clipped direct or on trays touching)			Ref. Methods 3 and 4 (enclosed in conduit etc, in or on a wall)			Ref. Methods 1, 11 and 12 (in trefoil)			Ref. Methods 1 and 11 (Flat and touching)		
1	2	3			4			5			6			7		
mm ²	mV/A/m	mV/A/m			mV/A/m			mV/A/m			mV/A/m			mV/A/m		
1.5	31	31			27			27			27			27		
2.5	19	19			16			16			16			16		
4	33	12			10			10			10			10		
6	7.8	7.9			6.8			6.8			6.8			6.8		
10	4.7	4.7			4.7			4			4			4		
16	2.9	2.9			2.9			2.5			2.5			2.5		
		r	x	z	r	x	z	r	x	z	r	x	z	r	x	z
25	1.85	1.85	0.31	1.90	1.85	0.190	1.85	1.60	0.27	1.65	1.600	0.165	1.600	1.600	0.190	1.600
35	1.35	1.35	0.29	1.35	1.35	0.180	1.35	1.15	0.25	1.15	1.150	0.155	1.50	1.150	0.180	1.150
50	0.99	1.00	0.29	1.05	0.99	0.180	1.00	0.87	0.25	0.90	0.860	0.155	0.870	0.860	0.180	0.870
70	0.68	0.70	0.28	0.75	0.68	0.175	0.71	0.60	0.24	0.65	0.590	0.150	0.610	0.590	0.175	0.620
95	0.49	0.51	0.27	0.58	0.49	0.170	0.52	0.44	0.23	0.50	0.430	0.145	0.450	0.430	0.170	0.460

120	0.39	0.41	0.26	0.48	0.39	0.165	0.43	0.35	0.23	0.42	0.340	0.140	0.370	0.340	0.165	0.380
150	0.32	0.33	0.26	0.43	0.32	0.165	0.36	0.29	0.23	0.37	0.280	0.140	0.310	0.280	0.165	0.320
185	0.25	0.27	0.26	0.37	0.26	0.165	0.30	0.23	0.23	0.32	0.220	0.140	0.260	0.220	0.165	0.280
240	0.19	0.21	0.26	0.33	0.20	0.160	0.25	0.185	0.22	0.29	0.170	0.140	0.220	0.170	0.165	0.240
300	0.155	0.175	0.25	0.31	0.16	0.160	0.22	0.150	0.22	0.27	0.140	0.140	0.195	0.135	0.160	0.210
400	0.12	0.140	0.25	0.29	0.13	0.155	0.20	0.125	0.22	0.25	0.110	0.135	0.175	0.110	0.160	0.195
500	0.093	0.120	0.25	0.28	0.105	0.155	0.185	0.100	0.22	0.24	0.090	0.135	0.160	0.088	0.160	0.180
630	0.072	0.100	0.25	0.27	0.086	0.155	0.175	0.088	0.21	0.23	0.074	0.135	0.150	0.071	0.160	0.170

Note :

r = conductor resistance at operating temperature

x = reactance

z = impedance



Rated Voltage



Standard



Flame Retardancy
NF C32-070-2.1(C2)
IEC60332-1-2/EN50265-2-1



Reduced Fire Propagation
NF C32-070-2.2(C1)
IEC60332-3-24
EN50266-2-4




Low Toxicity
NES 02-713/NF C 20-454



Low Corrosivity
IEC60754-2
EN50267-2-2/3
NF C 32-074



Low Smoke Emission
IEC 61034-1&2
EN 50268-1&2/NF C32-073



Halogen Free
IEC60754-1
EN50267-2-1