



Date: 1 Mar 11

Part No.: PT80273

CU/MICA/LSOH/OS/FRPVC


VERMIN-PROOF, UV RESISTING & FIRE RESISTING

TELEPHONE CABLE

Application:

This cable is used for communication and telephone systems and distribution cabling.

Construction:



Conductor:	Plain Annealed Solid Copper to IEC 228 Class 1
Fire Barrier:	Mica Tape.
Insulation:	LSOH
Twisting:	Two colored insulated conductors are uniformly twisted together to form a pair.
Shape:	Circular
Overall Screen:	Overall Polyester/ Aluminum foil screened plus 0.5mm ² copper drain wire
Outer Sheath:	Vermin-proof & UV Resistant FRPVC
Sheath color:	Black
Temperature Rating:	0 °C to 40 °C
Bending Radius:	6 x overall diameter

Marking: The cable is marked with white or other colors as follows:

- Caledonian Cables Co., Ltd
- Type and size of cable
- Manufacturing date
- Meter Marking

The meter mark is printed every meter with an accuracy of $\pm 0.5\%$.

Other printing are available according to customer request.



Caledonian

Phoenix Place North Street, Lewes, Sussex BN7 2QJ England Tel: +44 (0) 207 4195087 Fax: +44 (0) 207 8319489	Unit 1803 & 05, 18/F, Tower 3, Enterprise Square 1, No.9 Sheung Yuet Road, Kowloon Bay, HK Tel: +852 2116 1238 Fax: +852 2803 0726
---	--

Table 1. Technical Data

Number of Pair	Nom. Diameter of Conductor (mm)	Nom. Diameter of Cable (mm)
1	0.8	6.5
2	0.8	11.0
4	0.8	13.5

The data included in the present catalogue are merely indicative; Caledonian Cables Limited reserves to itself the right to change them as its own discretion in any time.